



## ARC 800

**Stud Welding Unit**  
for ARC stud welding  
according to current standards

### Technical Data

Gas/Automation	Series/Option	
Welding range	Dia. 14 GA to 3/8", #4 to 1/2" (dia. 2 to 10 mm, M3 to M12 (Type RD))	
Welding material	Mild steel, stainless steel	
Welding rate	7 to 17 studs/min (depending on application and stud dia.)	
Welding current	800 A	
Welding time	5 to 1,000 ms	
Primary power	230/460 V 3 phases, 50/60 Hz, 60/30 amp time delay fusing or 575 V, 3 phases, 50/60 Hz, 25 AT (alternative input voltages available)	
Power source	Transformer/Rectifier	
Cooling type	F (temperature controlled cooling fan)	
IP Code	IP 23	
Dimension L x W x H	18.50" x 9.06" x 8.66" (470 x 230 x 220 mm) without handle	
Weight	88 lbs	
Order No.	<b>230/460 V:</b> <b>93-16-0702A (Gas)</b> <b>93-16-0704A (Gas/Automation)</b>	<b>575V:</b> <b>93-15-0702A (Gas)</b> <b>93-15-0704A (Gas/Automation)</b>

### General Information

#### Application

- Especially suitable for thicker sheets of about 2 mm or higher

#### Process variants

- **Short cycle drawn arc welding**
- **Drawn arc welding**

#### Equipment

- **Welding with ceramic ferrule** (series)
- **Welding with shielding gas** (series)
- **Automatic** (optional)



## Advantages

### Features

- **Microcontroller** – for precise process times, optimal functional reliability and maximum operating convenience
- **Function monitoring** – automatic function test following power-up; monitoring of all internal system functions
- **Display of error codes** – on digital display
- **Lift test** – for gap welding guns and welding heads

### Structure

- **Extremely easy to operate**
- **Compact**
- **Robust** – metal housing withstands rough treatment in shop and on site

### Safety

- With integrated **mains filter** (protection against voltage peaks)
- **Optimal for construction sites with large mains voltage fluctuations** – use even with critical voltage supply (- 10 % + 10 %)
- **EMC test**
- **High-voltage test with log**
- **Retriggering lock-out** – prevents welding on a welding element that has already been set
- **Thermal monitoring of transformer** – automatic shutdown in case of overheating
- **Temperature-regulated ventilator** – reduces noise and dust in the stud welding unit (greater system reliability)
- **Consistent separation of transformer and control unit** – protects electronic components against dust and thermal loading
- **Control unit galvanically separated from welding lines** – high degree of functional safety
- **Cooling-air tunnel** – channelling of cooling air to the transformer protects electronic components against dirt and dust
- **Optimal protection against external interferences**
- **IP Code: IP 23**
- Also permits operation outdoors

### Welding

- **Display** – infinitely adjustable power setting; easy monitoring of all functions via LED displays; display of welding and gas-preflow time (optional: pneumatic feed time for automation); control and monitoring of all system functions
- **Powerful** – built-in power reserves
- **Trouble-free changing** of welding voltage polarity possible by reconnecting welding current and ground cables

### Suitable stud welding guns/ -heads

- **A 12, A 16, AI 06**
- **CA 08**
- **PAH-1 (only suitable for automatic version)**
- **KAH 412, KAH 412 LA (only suitable for automatic version)**

Issue 11/15  
(Technical data may change)